

SECTION 205-00 Driveline System — General Information

CONTENTS	PAGE
SPECIFICATIONS	205-00-2

SPECIFICATIONS**Material**

Item	Specification	Fill Capacity
Additive Friction Modifier XL-3 (US); CXL-3 (Canada)	EST-M2C118-A	118 ml (4 oz)
Motorcraft® High Contrast Hypoid Gear Marking Compound XG-14	—	—
Motorcraft® SAE 75W-140 Synthetic Rear Axle Lubricant XY-75W140-QL (US); CXY-75W140-1L (Canada)	WSL-M2C192-A and GL-5	8.8-in rear axle ^a
Premium Long-Life Grease XG-1-C or XG-1-K (US); CXG-1-C (Canada)	ESA-M1C75-B	—
Threadlock 262 TA-26	WSK-M2G351-A6	—

^a Service refill capacities are determined by filling the axle to the bottom of the filler hole. The vehicle must be on a level surface.

General Specifications

Item	Specification
Maximum driveshaft runout	0.89 mm (0.035 in)
Maximum pinion flange runout	0.25 mm (0.009 in)
Maximum transmission flange runout	0.20 mm (0.008 in)
Minimum rotational torque (Traction-Lok®)	27 Nm (20 lb-ft)